

For Your Reference Stations/Portable Base



ONE DEVICE, DUAL-PURPOSE

With a stable choke ring antenna installed outdoors, the SV100 can serve as a reference station, providing stable GNSS raw data for CORS network or deformation monitoring. In addition, with the detachable hook, SV100 can also be easily attached to the tripod as a portable base or RTK bridge. broadcasting correction data via 4G/UHF for your construction site or precision agriculture.

POWERFUL GNSS ENGINE

To ensure superior GNSS performance in all application scenarios, the SV100 is equipped with a high-precision GNSS engine for simultaneously tracking GPS, BDS, GLONASS, Galileo, QZSS & IRNSS. Embedded with multi-frequency anti-jamming technology, the SV100 offers high quality GNSS data even in complex environment.

FLEXIBLE CONFIGURATION

For professional users of reference stations, the web UI accessed via Ethernet/WiFi contains comprehensive status display, working modes and data transmission settings. For field users of portable base stations, SingularXYZ also provides an android app connected via Bluetooth, offering a clean interface for necessary functions.

+86-21-60835489

- +86-21-60835497
- ⊠ singularxyz@singularxyz.com

www.singularxyz.com



SingularXYZ Intelligent Technology Ltd. ② Floor 2, Building A, No. 599 Gaojing Road, 201702 Shanghai, China

SATELLITES TRACKING

Channels	1408
BDS	B1I, B2I, B3I, B1C, B2a, B2b
GPS	L1C/A, L1C, L2C, L2P(Y), L5
GLONASS	G1, G2, G3
Galileo	E1, E5a, E5b, E6
QZSS	L1C/A, L1C, L2C, L5
NavIC	L5
SBAS	WAAS, EGNOS, SDCM, BDSBAS, GAGAN
L-Band	Support
Cold start	<30s
RTK Initialization Time	<5s(typical)
RTK initialization reliability	>99.9%
Re-acquisition	<1s

ACCURACY

Standalone	1.5m Horizontally 2.5m Vertically
DGPS	0.4m Horizontally 0.8m Vertically
Static post-processing	2.5mm+0.5ppm Horizontally 5mm+0.5ppm Vertically
RTK	8mm+1ppm Horizontally 15mm+1ppm Vertically
PPP	5cm Horizontally 10cm Vertically
SBAS	< 1.0 m 3D RMS
Time Accuracy	20ns

COMMUNICATION

FDD-LTE B1/B3/B5/B7/B8 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA1x/CDMA2000 BC0/BC1	
 Working range: Up to 15km with optimal conditions Frequency range: 410-470MHz Protocol (TX & RX): LoRa Protocol(RX): TRIMATLK, TRANSEOT, SATEL, TRIMMARK3, etc. Channel spacing: 25KHz Transmit power: 0.5W~2W selectable 	
BT4.0 dual mode	
802.11 a/b/g/n/ac	
Support FTP download	
Support	
 1 10-pin connector, including 1 RS232, 1 PPS output, 1 USB and power supply 1 RJ45 for Ethernet 1 TNC connector for GNSS antenna 1 TNC connector for UHF antenna 1 SMA connector for 4G antenna 1 SIM card slot 	

DATA FORMAT

Data output format	- NMEA-0183 - Binary format *.xyz
Data update rate	1~50Hz selectable
Correction data format	RTCM v3.3/3.2/3.1/3.0
Network protocol	TCP, MQTT ² , Ntrip Server, Ntrip Caster

USER INTERACTION

LED indicators	4 LEDs indicating battery, satellite tracking, RTK status and network
WebUI	 Accessible via Wi-Fi, Ethernet Support configuration, status checking, data transfer, data storage and system upgrade
Power switch	Power switch on 10-pin cable

ELECTRICAL

Power consumption	3.5W
Input voltage	- Without battery: 9 - 28V DC - With internal battery: 9 - 22V
Battery (optional)	6600 mAh, support up to 13 hours working time.
MTBF	> 20000 hours

PHYSICAL

Size	162×142×65 mm, including connectors
Weight	1.05 kg without battery
Housing material	Aluminum alloy

DATA RECORDING

Storage	8 GB ³ , support loop recording
Storage format	RINEX 3.02/3.04, Binary format *.xyz

ENVIRONMENTAL

Working temperature	–40 °C to + 75 °C
Storage temperature	-55 ℃ to + 85 ℃
Humidity	95% non-condensing
Waterproof & dustproof	IP67
Drop	Designed to survive a 1m drop onto concrete
Vibration	MIL-STD-810

1. The enhanced UHF base is not compatible with normal UHF rovers on the market. For different user needs, SingularXYZ also provides normal UHF as an option compatible with UHF of other brands. Please clarify your requirements when placing the order.

2. The MQTT protocol is customizable.

3. Storage can be expanded to 32GB according to user demands.

All specifications are subject to change without notice.

©2025 SingularXYZ Intelligent Technology Ltd. All rights reserved. SingularXYZ [®] is the official trademark of SingularXYZ Intelligent Technology Ltd., registered in People's Republic of China, EU. All other trademarks are the property of their respective owners.



+86-21-60835497

⊠ singularxyz@singularxyz.com

www.singularxyz.com



SingularXYZ Intelligent Technology Ltd. \bigcirc Floor 2, Building A, No. 599 Gaojing Road, 201702 Shanghai, China