

SET1

ELECTRONIC THEODOLITE

Accurate Angles, Rugged Reliability



POWERFUL OPTICAL SYSTEM

The SET1 is equipped with a 30x magnification telescope and a 45mm objective aperture, providing superior clarity and precision for a wide range of surveying tasks. With a resolving power of 2.5" and a 1°30' field of view, it ensures clear and accurate measurements, even in challenging conditions.

PRECISE ANGLE MEASUREMENT

Featuring a high-precision electronic angle measurement system, the SET1 offers a minimum reading of 1"/5"/10" with an impressive accuracy of 2". The 71mm diameter circle and $\pm 3'$ vertical angle compensation ensure reliable and precise results, whether for construction or engineering applications.

BUILT FOR HARSH CONDITIONS

Designed to withstand demanding conditions, the SET1 boasts an all-metal body and reliable electronic incline sensor for vertical angle compensation. With a durable build and a long-lasting 1300mAH battery, it ensures consistent performance in tough outdoor environments, offering up to 10 hours of operation on a single charge.

TELESCOPE

Tube length	155mm
Objective aperture	45mm
Magnification	30x
Image	Erect
Field of view	1°30'
Resolving power	2.5"
Minimum focus	1.3 m
Stadia ratio	100
Stadia constant	0

PHYSICAL

Dimension	144×175×324mm
Weight	4.8 kg

All specifications are subject to change without notice.

©2025 SingularXYZ Intelligent Technology Ltd. All rights reserved. SingularXYZ® is the official trademark of SingularXYZ Intelligent Technology Ltd., registered in People's Republic of China, EU. All other trademarks are the property of their respective owners.

ELECTRONIC ANGLE MEASUREMENT

Minimum reading	1" / 5" / 10"
Accuracy	2"
Diameter of circle	71mm

COMPENSATOR

Electric incline sensor	Vertical angle compensation
Arrange	±3'
Minimum reading	1"

OPTICAL PLUMMET

Magnification	30x
Field of view	5°
Focusing range	0.5m ~ ∞

LEVEL SENSIBILITY

Plate level sensitivity	30"/ 2mm
Circular level sensitivity	8'/ 2mm

DISPLAY & ILLUMINATOR

Type	Two sides LCD
Reticle plate	Yes
Data export interface	Yes

ELECTRICAL

Voltage	DC 6.0V
Battery	- 1300mAH - 10hrs working time