

## PARTNERED PRODUCTS



### SingularPad Field Surveying Software

- Full Work Modes Support
- Various Survey & Stakeout Methods
- Bluetooth & Wi-Fi Connectivity
- Laser Surveying & Visual Targeting
- Real-time Visual AR Stakeout
- RTK Visual Photogrammetry
- Both GNSS receiver & Total Station Support



## SC260 DATA COLLECTOR



Powered by  
Android 11 OS

IP68  
IP68 & 1.5m  
anti-drop

4G  
VARIOUS  
communication



5.45  
inch  
5.45" sunlight-readable  
touch screen



9000mAh battery  
for 18h operating



4GB RAM + 64GB  
ROM + Extend TF

## Horus Visual & Laser GNSS Receiver

Version 12-09-2025

### SATELLITES TRACKING

Channels	1408
BDS	B1I, B2I, B3I, B1C, B2a, B2b
GPS	L1C/A, L1C, L2C, L2P(Y), L5
GLONASS	G1, G2, G3
Galileo	E1, E5a, E5b, E6
QZSS	L1C/A, L1C, L2C, L5
NavIC	L5
SBAS	WAAS, EGNOS, SDCM, BDSBAS, GAGAN
L-Band	Support
Cold start	<30s
RTK Initialization Time	<5s(typical)
RTK initialization reliability	>99.9%
Re-acquisition	<1s

### ACCURACY

Standalone	1.5m Horizontally 2.5m Vertically
DGPS	0.4m Horizontally 0.8m Vertically
Static Post-processing	2.5mm+0.5ppm Horizontally 5mm+0.5ppm Vertically
RTK	8mm+1ppm Horizontally 15mm+1ppm Vertically
PPP	5cm Horizontally 10cm Vertically
SBAS	< 1.0 m 3D RMS
Time Accuracy	20ns
Tilt Surveying	< ±2.5cm, within 60° Tilt Range
AR Stakeout	8mm+1ppm Horizontally 15mm+1ppm Vertically
Photogrammetry	2-5 cm @ 2-20 m range, typical
Laser tilt surveying	3 cm @ 10 m range, typical

### DATA FORMAT

Data Output Format	- NMEA-0183 - RINEX 3.02/3.04 - Binary Format *.xyz
Data Update Rate	1 ~ 50Hz Selectable
Correction Data Format	- RTCM v3.3/3.2/3.1/3.0
Supported Protocols	Ntrip client, Ntrip Server, Ntrip Caster, TCP, UDP

### COMMUNICATION

UHF Modem	- Frequency range: 410-470MHz - Protocol(RX): CSS,TRIMATLK, TRANSEOT, SATEL,TRIMMARK3, etc. - Channel spacing:25KHz - Receive Only
Bluetooth	BT4.0 Dual Mode

NFC	Support NFC Connection
WiFi	802.11 a/b/g/n/ac
Interface	- 1 Type-C Interface for Data Transmission and Charging - 1 SMA Connector

### HARDWARE

Platform	Quad-core 1.5GHz CPU, 2.0Tops NPU
Laser Sensor	- Class 3R, avoid direct eye exposure - Range: 50m
Camera	- Dual-camera with 2MP global shutter - Frame: 25 fps

### USER INTERACTION

Front panel	- 3 LED indicators indicating satellite tracking, differential data and power - 1 button for power on/off
WebUI	- Accessible via Wi-Fi - Support Configuration, Status Checking, Data Chekcing, Data Storage and System Upgrade

### ELECTRICAL

Power Consumption	> 3.5 W <sup>2</sup>
Battery	- 6600 mAh, up to 12 hours working time - Fast charge of 3.5 hours charging time

### PHYSICAL

Size	Φ133 mm × 72 mm
Weight	> 850 g
Storage	8 GB <sup>3</sup>
Housing Material	Magnesium-aluminum Alloy

### ENVIRONMENTAL

Working Temperature	-30 °C to + 65 °C
Storage Temperature	-55 °C to + 85 °C
Humidity	100% Non-condensing
Waterproof & Dustproof	IP67
Drop	Designed to Survive a 2m Drop onto Concrete

1. The power consumption varies with the different work modes.
2. Storage can be expanded to 32GB according to user demands.

All specifications are subject to change without notice.  
©2025 SingularXYZ Intelligent Technology Ltd. All rights reserved. SingularXYZ® is the official trademark of SingularXYZ Intelligent Technology Ltd., registered in People's Republic of China, EU, USA. All other trademarks are the property of their respective owners.

+86-21-60835489  
+86-21-60835497  
singularxyz@singularxyz.com  
www.singulz

**SingularXYZ**  
SingularXYZ Intelligent Technology Ltd.

# Horus

## VISUAL & LASER GNSS RECEIVER

Redefining Measurement With Vision



## HORUS VISUAL & LASER GNSS RECEIVER

The Horus GNSS receiver combines strong GNSS engine, new-gen IMU, versatile work modes and leading-edge visual & laser technologies in a compact, rugged housing, bringing an efficient, precise and smart surveying experience for professionals.

By fusing dual cameras and a laser sensor, Horus enables immersive AR stakeout, non-contact laser surveying with visual aiming, and high-precision photogrammetry—expanding the capabilities of traditional RTK surveying.

**Full-Constellation**  
1408 channels track GPS, BDS, GLONASS, Galileo, QZSS, NavIC, and SBAS simultaneously, delivering centimeter-level accuracy.

**Versatile Connectivity**  
Support Bluetooth/WiFi/NFC/USB connectivity, you can easily interact with Horus in various ways by different purpose.

**12Hrs Battery Life**  
Built-in battery with 6600mAh large capacity support more than 12 hrs working time and only 3.5hrs charging time.

**Web UI Access**  
Access via WiFi to configure work modes, download data, upgrade firmware, and check device status through a web interface.

**Next-Gen IMU**  
New-generation IMU enhances reliability and integrates with pole surveying, AR stakeout, laser surveying, and photogrammetry.



## SEE CLEARER, MEASURE FURTHER

Hard-to-Reach Points, Hazardous Areas, GNSS-Denied Zones - Measured with Ease!

### Non-Contact Laser Surveying

**Precise Laser Surveying** ▼  
Visible green laser delivering centimeter-level accuracy



**Camera-Assisted Targeting** ▶  
See clearly, aim precisely - no matter the distance



### Visual Photogrammetry

▲ **HD Starlight-Grade Camera**  
Capture clear, detailed images anytime

◀ **Tap & Measure on SingularPad**  
Instant centimeter-level photogrammetry



## INTUITIVE AR VISUAL STAKEOUT

Stake What You See, Boost Efficiency by Over 50%



Long-Range Targeting with Precision Guidance



Close-Range Stakeout with Immersive AR View




**Auto-Switch Based on Distance**  
Always the Best View for Every Stakeout Point

## VISUAL DATA READY FOR 3D MODELING

From Visual Capture to Seamless Modeling



▲ **Integrated Camera For Visual Data Capture**



▲ **Compatible With Leading 3D Modeling Software**